




INSTALLATION INSTRUCTIONS

VENEZIA ACRYLIC BATHS

	DESCRIPTION	SIZE	CODE	
VENEZIA RANGE	Freestanding model 	1580 x 730 x 590	JBFS158	
		1680 x 750 x 590	JBFS168	
	Corner model (RH/LH) 	1500 x 700 x 590	JBCR150	JBCL150
		1700 x 750 x 590	JBCR170	JBCL170
	Back to wall model 	1500 x 700 x 590	JBBTW150	
		1700 x 800 x 560	JBBTW170	

PREPARATION:

- Refer to the relevant Technical Data Sheet for dimensions and other important information
- Installation must be carried out by a qualified tradesman in accordance with all local regulations
- Waterproofing must be done by a suitably qualified tradesman in accordance with AS 3740 and
- Ensure the tapware is correctly located for the bath
- Ensure that the floor drainage is suitably located and appropriately installed

INSTALLATION STEPS:

- HANDLE WITH CARE to prevent any damage.
- Carefully remove the bath from its packaging. This should be a two-man job due to its size and weight.
- Check for any visible signs of damage and if found contact the supplier immediately. Claims for damage after installation will not be accepted.
- Ensure that all supplied components are accounted for.
- Line the bath with soft protective material to prevent damage during installation.

1. Place the bath in position
2. Use a spanner to adjust the feet so that the bath is level (this is essential to ensure proper drainage)
3. Install the 40mm plug, waste and overflow and connect to the floor waste - test the bath for drainage and leaks
4. When the bath is in its final position apply silicone to the bath to wall/floor joins - allow 24 hours for curing before use

CARE AND CLEANING

This bath is manufactured using sanitary grade cross-linked acrylic material, this is a durable material but avoid contact with naked flames, cigarettes nail polish remover and any strong chemicals or solvents.

Recommendations:

- To fill the bath, start with cold water before adding hot - this minimises thermal stresses to the bath.
- Clean the bath after use with a soft cloth and warm soapy water - this removes oils and soap residues that may build up on the acrylic surface.
- To preserve the polished surface only use soapy water/mild detergent for cleaning.
- DO NOT use abrasive cleaners, powders, pastes, creams, scouring pads, chemicals or window cleaning sprays.
- To remove stubborn marks cream-type cleaners may be used with care. Scratches can be removed with fine polish such as 'Brasso'.

